

TECHNICAL CARD



LED Portable Flashlight

VIDEX®



WARRANTY 3 YEARS



Cold White / Zimna biel / Studena bila / Blanc froid / Studená biela / Koud wit / Hideg feher / Hladno bela / Hladno bijela / Kaltweiß / Alb rece / Šalta balta / Auksti balta / Kūlm valge.

General parameters

Light source replaceable no

Type of light source

Dimmable no

Technology LED

Electrical parameters

On-mode power (Pon) 10 W

Input interface USB-C

Photometric parameters

Correlated color temperature 5700K (cold white)

Useful luminous flux of the contained light source (Φuse) 600 Lm

Peak luminous intensity 3320 cd

Additional information

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion 16340
Battery voltage	3.7 V
Battery capacity	800 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP68
Housing material	Aviation anodized aluminum

Dimensions

EAN	4820246481045
Width	24 mm
Height	74.5 mm
Depth	27 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	44g

Signs marking goods

Packaging marking CE, Utilization

VIDEX®

VIDEX VLF-A055 600Lm 5700K


INDEX: VLF-A055

VIDEX®**VIDEX VLF-A055 600Lm 5700K****INDEX: VLF-A055**

VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



VIDEX®
MODEL | A055

ULTRACOMPACT RECHARGEABLE
LED FLASHLIGHT



600
MAX LUMENS



4
LIGHTING
MODES



TYPE-C



2m
IP68



1m
IMPACT
RESISTANCE

VIDEX®
MODEL | A055




LUMINUS SST20
10W
5700K

Energy efficient led provides maximum output 600 lumens,
beam distance 115m and long service life up to 50000 hours.

VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055



VIDEX®

VIDEX VLF-A055 600Lm 5700K

INDEX: VLF-A055

VIDEX®
MODEL | A055



High-quality copper conducts current better and retains elasticity over the years compared to cheaper metals.

VIDEX®
MODEL | A055



WITH BATTERY 800mAh

	HIGH	LOW	MOON	STROBE
OUTPUT	600 Lm	150 Lm	30 Lm	600 Lm
RUNTIME	1h 40min	2h 45min	13h	1h 40min
DISTANCE	115m	54m	20m	115m
INTENSITY	3320cd	640cd	300cd	3320cd

Protection against over charge, over discharge, wrong polarity.

VIDEX®
MODEL | A055

PROGRAM ROOT



Start position: OFF → Action A: Click → Result: > ON > HIGH > LOW > MOON > STROBE > OFF >

** HIGH / LOW / MOON / STROBE → Press and hold for 0.5 sec → OFF ** → Press and hold for 0.5 sec → ON **

** The current mode memorized and applied next time when turned on.
Note: Battery indication is always on if the light is switched on.

VIDEX®
MODEL | A055

KIT CONTENT



SPARE SILICONE RINGS

USER'S MANUAL, WARRANTY CARD | LI-ION BATTERY | FLASHLIGHT | LANYARD | CHARGING CABLE

SIZE 74.5x24x27mm
WEIGHT 44g (without battery)

We reserve the right to make technical changes. The data contained in this material is not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11,
30-732 Krakow, Poland.

INDEX: VLF-A055



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



— The protection is effective in case of a fall from a height of up to 1 meter



— The product is incompatible with light regulators



— Operating temperatures range



— The product does not contain mercury



— Class of protection against dust and moisture.
The product has full protection against dust and prolonged immersion in water at a depth of more than 1 meter