

INDEX: VLF-H055D

TECHNICAL CARD



LED Headlamp



VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D

1m SHOCK RESISTANT









WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	5 W x 2
Input interface	USB-C

Photometric parameters

Correlated color temperature	5000K (neutral white)
Useful luminous flux of the contained light source (Φ use)	500 Lm
Peak luminous intensity	3280 cd

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion VLF- B12, AAA disposable battery
Battery voltage	3.7 V, 1.5 V
Battery capacity	1200 mAh
Battery indicator	4 level
Battery replaceable	yes
Mercury content	Does not contain
Ingress protection	IP65
Housing material	PC

Dimensions

EAN	4820246483100
Width	60 mm
Height	45 mm
Depth	48 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	72g

Signs marking goods

Packaging marking	CE, Utilization





INDEX: VLF-H055D











VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D















We reserve the right to make technical changes. The data contained in this material is

VIDEX VLF-H055D 500Lm 5000K

INDEX: VLF-H055D

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.



The product meets the requirements of EU directives



It is forbidden to throw away waste equipment marked with the symbol of a crossed-out bin with other waste



The protection is effective in case of a fall from a height of up to 1 meter



The product is incompatible with light regulators



Operating temperatures range



- The product does not contain mercury



Class of protection against dust and moisture.

The product has full protection against dust and water jets from all directions

Date: 18.03.2025