

INDEX: VLF-H045Z

TECHNICAL CARD



LED Headlamp



Pursuant to the provisions of the WEEE Act, it is forbidden to put waste equipment marked with the symbol of a crossed out bin together with other waste. The user, wishing to get rid of electronic and electrical equipment, is obliged to return it to a waste equipment collection point. There are no hazardous components in the equipment that have a particularly negative impact on the environment and human health.





WARRANTY 2 YEARS



Neutral White / Neutralny biały / Neutralni bila / Blanc neuter / Neutrálna biela / Neutraal wit / Semleges feher / Nevtralno bela / Neutralno bijela / Neutralweiß / Alb neutru / Neutralus balta / Neitrāls balta / Neutraalne valge / Неутрално бяла / Bianco neutro.

General parameters

Light source replaceable	no

Type of light source

Dimmable	no
Technology	LED

Electrical parameters

On-mode power (Pon)	5 W
Input interface	Micro USB

Photometric parameters

Useful luminous flux of the contained light source (Фиse)	270 Lm
Correlated color temperature	5000K (neutral white)
Peak luminous intensity	700 cd

VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z

IP65

Additional information

Housing colour	Black
Fall protection	1 m
Operating temperature range	-20° +40°C
Battery type	Li-ion
Battery voltage	3.7 V
Battery capacity	1800 mAh
Battery indicator	5 level
Battery replaceable	no
Mercury content	Does not contain
Ingress protection	IP65
Housing material	РС

Dimensions

EAN	4820246481052
Width	70 mm
Height	46 mm
Depth	38 mm
In the package	1 pc.
Outer box	20 pcs.
Unit nett weight	122g

Signs marking goods

Packaging marking

CE, Utilization



VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z











VIDEX VLF-H045Z 270Lm 5000K

INDEX: VLF-H045Z







INDEX: VLF-H045Z

not legally binding.

Allegro opt Sp. z o.o., ul. Mierzeja Wiślana 11, 30-732 Krakow, Poland.

CE	ne product meets the requirements of EU directives
🛛 🗶 ma	is forbidden to throw away waste equipment arked with the symbol of a crossed-out bin with her waste
SHOCK RESISTANT	The protection is effective in case of a fall from a height of up to 1 meter
Not Dimmable	The product is incompatible with light regulators
°C	Operating temperatures range
Free	The product does not contain mercury
IP65	Class of protection against dust and moisture. The product has full protection against dust and water jets from all directions

We reserve the right to make technical changes. The data contained in this material is